



- NOTE
- 1) VERIFY HEATER VOLTAGE PRIOR TO CONNECTING TO POWER SOURCE.
  - 2) POWER SOURCE AC SUPPLY 230VAC +5%/-10%, 115VAC +5%/-10%

CONTROLLED DRAWING

This is a registered part with FM/UL for use on an approved/ listed fire pump driver. No substitutions are allowed. Consult engineering prior to and regarding any change.

E	ADDED OPTIONAL LUBE OIL HEATER	ASC	KJK	11MAR08
D	REVISED INTERCONNECTIONS	KJK	JTW	06DEC99
C	ADDED NOTE DETAIL	GLH	JTW	01SEP98
SYM	REVISION	ENGR	APVD	DATE

THIS DRAWING AND THE INFORMATION HEREIN ARE OUR PROPERTY AND MAY BE USED BY OTHERS ONLY AS AUTHORIZED BY US. UNPUBLISHED--ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.	DWN	DMPOTTER
	DATE	01MAR94
	ENGR	JTWHITNEY
	CHK	
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:	MM	IN
DECIMAL	.X ±1.5 ±0.06	
	.XX ±0.8 ±0.03	
	.XXX ±0.25 ±0.01	
FRACTIONAL	±1/32	
ANGULAR	±.5°	
USAGE: 1000 SERIES	INSP	Y
	SERIES CODE	MP

**CLARKE**  
Fire Protection Products, Inc.

NAME: WIRING DIAGRAM, KIM JACKET WATER HEATER 120/240VAC - 1500 WATTS

SIZE: A PART NO. C07591 REV. E

SCALE: NONE UNITS: NONE

SHEET 1 OF 1