

# CLARKE UK, LTD.

**Diesel Fire Pump Drivers  
Radiator Cooled  
Power Ratings and Models - Summary  
UK Purchased  
Non-Listed Engines built to Specific Country Code Requirements**

Non-Listed (NL) - Gross Power Ratings Radiator Cooled Engines											
MODEL	Speed (RPM) & Power (kW/BHP)										
	1760	1800	2000	2100	2200	2350	2400	2600	2800	2960	3000
JU4R-NL09	32	33	37	40	41	42.5					
	43	44	50	53	54.5	57					
JU4R-NL11						42.5	43	45.5			
						57	58	61			
JU4R-NL13									54	54	54
									73	73	73
JU4R-NL19	48	48.5	51.5	53	54	56					
	64	65	69	71	72.5	75					
JU4R-NL21						56	56	58			
						75	75.5	77.5			
JU4R-NL23									63	64	64
									84	86	86
JU4R-NL40	77	80	83.5	86	86.5	87					
	103	104.5	112	115.5	116	117					
JU4R-NL49	87	89	97	101	99	96					
	117	119	130	135	132.5	129					
JU4R-NL51						98	98	98			
						131	131	131			
JU4R-NL53									111	109	109
									148.5	146	146

A 10% deduction, from the above charts, must be made to determine maximum allowable power available for maximum fire pump load. **(Gross power / 1.1 = Net Power)**  
 All engines will be provided with a nameplate indicating the Gross and the Maximum Allowed Pump Load power ratings.  
 All above engines and ratings are for Emergency Stand-By-Fire Protection application use only.  
 Additional de-rate for operating ambient temperature and elevation required.

**Contact Clarke UK - Coatbridge, UK ~ Phone +44.1236.429.946 Fax +44.1236.427.274**