

**Diesel Fire Pump Drivers
Heat Exchanger Cooled
Power Ratings and Models - Summary
UK Purchased**

Meeting NFPA-20, Underwriters Laboratories (ULI & cUL) and Factory Mutual (FM)

MODEL	UL/FM						
	Certified Speed (RPM) & Power Rating (kW/BHP)						
	1470	1760	2100	2350	2600	2800	3000
JU4H-UF10		31 / 41	38 / 51	41 / 55			
JU4H-UF12				41 / 55	44 / 59		
JU4H-UF14				41 / 55	44 / 59	52 / 70	53 / 71
JU4H-UF20		45 / 60	50 / 67	54 / 72			
JU4H-UF22				54 / 72	56 / 75		
JU4H-UF24				54 / 72	56 / 75	60 / 80	62 / 83
JU4H-UF30		48 / 64	59 / 79	63 / 85			
JU4H-UF32				63 / 85	63 / 85		
JU4H-UF34				63 / 85	63 / 85	78 / 104	86 / 115
JU4H-UFH8	47 / 63	54 / 73					
JU4H-UFH0		54 / 73	66 / 88	73 / 98			
JU4H-UFH2				73 / 98	74 / 99		
JU4H-UF40		70 / 94	78 / 105	79 / 106			
JU4H-UF42				79 / 106	79 / 106		
JU4H-UF50		82 / 110	97 / 130	95 / 127			
JU4H-UF52				95 / 127	95 / 127		
JU4H-UF54				91 / 122	104 / 139	108 / 145	108 / 145
JU6H-UFD0		82 / 110	107 / 144	110 / 148			
JU6H-UFD2				110 / 148	110 / 148		
JU6H-UF30	70 / 94	104 / 140	119 / 160	119 / 160			
JU6H-UF32				119 / 160	119 / 160		
JU6H-UF34				119 / 160	119 / 160	119 / 160	131 / 175
JU6H-UFG8	97 / 130	111 / 149					
JU6H-UFABL8	101 / 136	129 / 173					
JU6H-UFABL0		129 / 173	129 / 173	129 / 173			
JU6H-UFABL2				129 / 173	129 / 173		
JU6H-UFM8	101 / 136	131 / 175					
JU6H-UFM0		131 / 175	154 / 207	149 / 200			
JU6H-UFM2				149 / 200	149 / 200		
JU6H-UF58	103 / 138	137 / 183					
JU6H-UF50		137 / 183	157 / 210	157 / 210			
JU6H-UF52				157 / 210	157 / 210		
JU6H-UF54				157 / 210	161 / 216	161 / 216	161 / 216
JU6H-UF60		149 / 200	179 / 240	179 / 240			
JU6H-UF62				179 / 240	179 / 240		
JU6H-UF84				181 / 243	184 / 247	193 / 259	205 / 275
JU6H-UFKAPG	164 / 220						
JU6H-UFKAQ8		169 / 227					
JU6H-UFKARG		188 / 252					
JU6H-UFKAS0			194 / 260				
JW6H-UF30	164 / 220	198 / 265	205 / 275	205 / 275			
JW6H-UF40	179 / 240	216 / 290	224 / 300	224 / 300			
JW6H-UF50		224 / 300	254 / 340	261 / 350			
JW6H-UF60		269 / 360	280 / 375	269 / 360			
JW6H-UFAAM8		278 / 373					
JW6H-UFAA80		315 / 422	298 / 400				
DR8H-UFAA40	287 / 385	343 / 460	365 / 490	365 / 490			
DR8H-UFAA5G	336 / 450						
DR8H-UFAA68		369 / 495					
DR8H-UFAA62			373 / 500	373 / 500			
JX6H-UFAD60		380 / 510	392 / 525				
JX6H-UFADN0		404 / 542	429 / 575				
DS0H-UFAAN0		404 / 542	429 / 575				
JX6H-UFADP0		429 / 575	447 / 600				
DS0H-UFAA68	389.5 / 522	438 / 587					
DS0H-UFAA60			458 / 614	452 / 606			
JX6H-UFAD88		460 / 617					
DT2H-UFAA60	541 / 725	600 / 805	656 / 880				
DT2H-UFAA98	615 / 825	732 / 982					
DT2H-UFAA92			764 / 1025				

CLARKE UK, LTD.

***Diesel Fire Pump Drivers
Heat Exchanger Cooled
Power Ratings and Models - Summary
UK Purchased***

Meeting NFPA-20, Underwriters Laboratories (ULI & cUL) and Factory Mutual (FM)

Maximum pump load may equal the ratings shown in charts above.
All above engines and ratings are for Emergency Stand-By Fire Protection application use only.
Caution: JU6H-UF34, 54 and 84 engines cannot be used between 2650 and 2750 rpm.
Additional de-rates for site operating ambient temperature and elevation required

Contact Clarke UK - Coatbridge, UK ~ Phone +44.1236.429.946 Fax +44.1236.427.274