

# **CLARKE UK, LTD.**

**Diesel Fire Pump Drivers  
Radiator Cooled  
Power Ratings and Models - Summary  
UK Purchased**

Meeting NFPA-20, Underwriters Laboratories (ULI & cUL) and Factory Mutual (FM)

UL/FM						
RADIATOR COOLED MODEL	Certified Speed (RPM) & Nameplate Power (kW/BHP)					
	1760	2100	2350	2600	2800	3000
JU4R-UF09	29 / 39	36 / 48	39 / 52			
JU4R-UF11			39 / 52	41 / 55.5		
JU4R-UF13					50 / 66.5	50 / 66.5
JU4R-UF19	44 / 58.5	48 / 64.5	51 / 68			
JU4R-UF21			51 / 68	53 / 70.5		
JU4R-UF23					57 / 76.5	58 / 78
JU4R-UF40	70 / 94	78 / 105	79 / 106			
JU4R-UF49	79 / 106	92 / 123	87 / 117			
JU4R-UF51			89 / 119	89 / 119		
JU4R-UF53					101 / 135	99 / 133

Maximum pump load may equal the ratings shown in charts above.  
All above engines and ratings are for Emergency Stand-By Fire Protection application use only.  
Additional de-rates for site operating ambient temperature and elevation required

Contact Clarke UK - Coatbridge, UK ~ Phone +44.1236.429.946 Fax +44.1236.427.274